

EVINRUDE® ENGINE SPECIFICATIONS

E 15

Engine Model	E15RG4 <input type="checkbox"/> E15RGL4 <input type="checkbox"/> E15PGL4 <input type="checkbox"/>
Colour	Graphite
Engine Type	2-cylinder
Bore x Stroke - mm	61 x 60
Displacement - cc	351
Gear Ratio	2.15:1
Full Throttle RPM Range	5000-6000 RPM
Weight - kg	52 <input type="checkbox"/> 53 <input type="checkbox"/> 55 <input type="checkbox"/>
Starting	Manual <input type="checkbox"/> Electric <input type="checkbox"/>
Controls	Mechanical
Fuel Induction	Carbureted
Alternator Output	Only on Electric Models: 12V, 145W, 12A (optional on Electric Start Models)
Steering	Tiller <input type="checkbox"/> Remote <input type="checkbox"/>
Trim Method	Manual or Power Tilt
Shaft Length - in	15 <input type="checkbox"/> 20 <input type="checkbox"/>
Oil Tank Capacity - ml	950
Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Recommended Fuel	87 Octane
Warranty	3-Year, Non-Declining
Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union



EVINRUDE®

